

COURT PRO 19

SPECIFICATION SHEET



MULTISPORT | TENNIS



PRODUCT SPECIFICATION +/- 10%

Tuft Height	Stitch Rate	Yarn Weight	Total Product Weight	Machine Gauge	Roll Width	Shipping Weight**
19mm	230	1,000 g/sq m	1,735 g/sq m	3/8"	3.71m*	6.588 kg/LM

YARN CHARACTERISTICS

Yarn 1	PE Fibrillated
Yarn 2	N/A
Yarn 3	N/A
Stand Total Dtex	8,900
Colour	Olive Green, Brick, Dark Blue, Field Green, Light Blue, Red
Line Colours	White, Yellow, Red, Light Blue, Dark Blue

BACKING CHARACTERISTICS

Primary Backing	100% woven PP, UV resistant
Secondary Backing	
Backing Compound	High performance latex compound, specifically designed for sports products and bespoke to Grassports

PARTICULATE INFILL

Stabilising Infill			Performance Infill			Total
Sand Type	Sand Size	Sand Infill Height	Infill Type	Infill size	Infill Height	Infill Height
Rocla 40	Upon Request	18mm (min)	N/A	N/A	N/A	18mm

FIRE RATING

Critical Radiant Flux (kW/m ²)	Infill Sand Requirement (kg/m ²)	Smoke Development Rate (% min)	Building Type
N/A	N/A	N/A	N/A

RECOMMENDED BASE CONSTRUCTION

This system can be laid on concrete, asphalt or crushed rock.

SHOCKPAD OPTIONS

- 10mm preformed rubber roll out pad
- 8mm Trocellen C9008XC roll out pad
- 15mm rubber insitu pad
- Trocellan C5008XC roll out pad
- Sine roll out pad

INSTALLATION & MAINTENANCE

Please refer to the relevant Installation and Maintenance Guides for full details. For further information contact Grassports.

CERTIFICATIONS

N/A

WARRANTY

Grassports offer a 10 year conditional warranty with Grassports Court Pro 19, please refer to Grassports for a copy of our warranty. Refer to Installation and Maintenance Guides for details.



* 3.66m usable ** incl. core